

The best Ignition Module for your application



Unit and Features	Maximum Engine Size	Maximum Cylinder Number	GT 6	GT 8	GT 12	GS 8	GS 12
GT 6	800in ³ /19lts	6					
GT8	All	8					
GT12	All	12					
GS 8	All	8					
GS 12	All	12					
Maximum Speed			4,000	4,000	4,000	4,000	4,000
Connector Size			18 Pin	36 Pin	36 Pin	36 Pin	36 Pin
Software Programme			Gillfire	SparkZ	SparkZ	SparkZ	SparkZ
Fully Configurable			●	●	●	●	●
Data Logging			●	●	●	●	●
9-30V DC			●	●	●	●	●
Single Pickup			●	●	●	●	●
SM 60 Coils			●	●	●	●	●
Timing Maps			●	●	●	●	●
Dual Fuel Switch			●	●	●	●	●
Global Timing Adjust			●	●	●	●	●
Tachometer Output			●	●	●	●	●
Ground Shutdown				●	●	●	●
Load / Timing				●	●	●	●
Individual Cyl Timing				●	●	●	●
Display				●	●	●	●
CY 90 or Mach A coils				●	●	●	●
Dual Pickup						●	●
CSA Approved						●	●
EH 12 Compatible						●	●
Prog / User Interface						●	●
Sec Diag Standard						●	●

* Please contact Gill regarding engines that may qualify for wasted spark applications

➤ More information at gillsc.com

E support@gillsc.com

T +44 (0)1590 613900

GILL

Sensors & Controls